



**EF 8-15mm f/4L Fisheye USM  
Specification Sheet**

| Optical Features/Specifications                |  |
|--|--|
| Angle of view (horizontal, vertical, diagonal) | 180° - 142°,<br>180° - 91° 46',<br>180° - 175° 30' |
| Lens construction (elements/groups)            | 14/11  |
| No. of diaphragm blades                        | 7  |
| Minimum aperture                               | 22   |
| Closest focussing distance (m)                 | 0.15m  |
| Maximum magnification (x)                      | 0.39 (at 15mm)                                     |
| Distance Information                           | Provided   |
| AF actuator                                    | Ring USM <sup>3</sup>                              |
| Physical Specifications                        |  |
| Dust/moisture resistance <sup>4</sup>          | Yes  |
| Filter diameter (mm)                           | Filter Holder                                      |
| Max. diameter x length (mm)                    | 78.5 x 83  |
| Weight (g)                                     | 540  |
| Accessories                                    |  |
| Lens Cap                                       | Lens Cap 8-15                                      |
| Lens hood                                      | EW-77 (15mm only)                                  |
| Lens case/pouch                                | LP1219   |
| Extender Compatibility                         | NC   |

All data is based on Canon standard testing methods except where indicated.  
Subject to change without notice.

<sup>3</sup> Full time Manual focus

<sup>4</sup> Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.