

# EOS R

**CAPTURE THE  
FUTURE**

## A pioneering full-frame EOS R camera for professionals and advanced enthusiasts

Building on over 30 years of EOS innovation and design heritage, EOS R sets the standard for the camera of tomorrow with a pioneering lens mount, offering responsive, high-speed auto-focus in as little as 0.05 seconds\*.



- Greater creativity thanks to pioneering technology
- Capture more detail in photographs and video
- Use your EF and EF-S lenses via an adapter plus innovative RF optics
- Refined, responsive handling and ergonomics
- Connect and share images and movies with ease
- Shoot professional 4K video for breath-taking films

*\*Measured using CIPA-compliant guidelines, and internal measurement method with the lens RF24-105mm f/4 L IS USM mounted with one-shot AF in use.*

**Canon**

---

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS R

# CAPTURE THE FUTURE

<b>IMAGE SENSOR</b>		<b>WHITE BALANCE</b>	
<b>Type</b>	36 x 24 mm CMOS	<b>Type</b>	Auto white balance with the imaging sensor
<b>Effective Pixels</b>	Approx. 30.3 megapixels	<b>Settings</b>	AWB (Ambience priority/White priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour temperature Setting
<b>Total Pixels</b>	Approx. 31.7 megapixels		White balance compensation:
<b>Aspect Ratio</b>	3:2		1. Blue/Amber +/-9
<b>Low-Pass Filter</b>	Built-in/Fixed		2. Magenta/ Green +/-9
<b>Sensor Cleaning</b>	EOS integrated cleaning system	<b>Custom White Balance</b>	Yes, 1 setting can be registered
<b>Colour Filter Type</b>	Primary Colour	<b>WB Bracketing</b>	+/-3 levels in single level increments
			3, 2, 5 or 7 bracketed images per shutter release
<b>IMAGE PROCESSOR</b>			Selectable Blue/Amber bias or Magenta/Green bias
<b>Type</b>	DIGIC 8		
		<b>VIEWFINDER</b>	
<b>LENS</b>		<b>Type</b>	0.5-type OLED colour Electronic Viewfinder
<b>Lens Mount</b>	RF (EF and EF-S lenses can be attached using Mount Adapter EF-EOS R, Control Ring Mount Adapter EF-EOS R, Drop-In Filter Mount Adapter EF-EOS R. EF-M lenses not compatible)	<b>Dot Count</b>	3.69 Million dots (1280 x 960)
		<b>Coverage (Vertical/Horizontal)</b>	Approx. 100%
<b>Focal Length</b>	Equivalent to 1.0x the focal length of the lens with RF and EF lenses 1.6x with EF-S	<b>Magnification</b>	Approx. 0.76x (4)
		<b>Dot Count</b>	3.69 Million dots (1280 x 960)
<b>FOCUSING</b>		<b>Eyepoint</b>	Approx. 23mm (from eyepiece lens centre)
<b>Type</b>	Phase-difference detection system with image sensor (Dual Pixel CMOS AF)	<b>Dioptr Correction</b>	-4 to +2 m <sup>-1</sup> (dioptr)
		<b>Viewfinder Information</b>	AF point information, Exposure level indicator, Number of remaining multiple exposures, Exposure compensation, HDR shooting, Highlight tone priority, Multiple-exposure shooting, ISO speed, Dual Pixel RAW shooting, Possible shots, Multi Shot Noise Reduction, Number of self-timer shooting, Digital Lens Optimizer, Maximum burst, AF method, Battery level, AF operation, Exposure simulation, Drive mode, AEB, Metering mode, FEB, Anti-flicker shooting, Still photo cropping, Shooting mode, Aspect ratio, Scene icons
<b>AF Zones</b>	With Area 88% horizontal and 100% vertical		Auto Lighting Optimizer, AE lock Picture Style, Flash-ready, White balance, Flash off White balance correction, FE lock, Image Quality, High-speed sync, Bluetooth function, Shutter speed, Wi-Fi function, Multi-function lock warning, Histogram, Aperture Electronic level, Lens information
<b>AF working range</b>	EV -6 to 18 (23 °C, ISO 100)	<b>Depth of field preview</b>	Yes, via customised button
<b>AF Modes</b>	One-Shot AF, Servo AF		
<b>AF Point Selection</b>	Automatic selection: Face + tracking, 143 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 5655 AF positions available Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding Manual selection: Zone AF (all AF points divided into 9 focusing zones) Manual selection: Large Zone AF (Vertical) Manual selection: Large Zone AF (Horizontal)	<b>LCD MONITOR</b>	
		<b>Type</b>	8.01 cm (3.15") Clear View LCD II, approx. 2.1 million dots. Vari-Angle
<b>AF Lock</b>	Locked when shutter button is pressed halfway or AF ON is pressed in One Shot AF mode. Using customised button set to AF stop in AI servo	<b>Coverage</b>	Approx. 100%
		<b>Viewing Angle (horizontally/vertically)</b>	Approx. 170° vertically and horizontally
<b>AF Assist Beam</b>	Emitted by built in LED or optional dedicated Speedlite (flash)	<b>Coating</b>	Anti-reflection and Anti-smudge. Reinforced glass incorporated
<b>Manual Focus</b>	Selected on lens	<b>Brightness Adjustment</b>	Manual: Adjustable to one of seven levels Colour Tone Adjustment: 4 settings
		<b>Touch-screen operations</b>	Capacitive method with menu functions, Quick Control settings, playback operations, and magnified display. AF point selection in still and Movies, touch shutter is possible in still photo shooting
<b>EXPOSURE CONTROL</b>		<b>Display Options</b>	(1) Basic Camera settings (2) Advance Camera settings (3) Camera settings plus histogram and dual level display (4) No info (5) Quick Control Screen
<b>Metering modes</b>	Real-time with image sensor, 384-zone metering. (1) Evaluative metering (linked to All AF points) (2) Partial metering (approx. 6.1% of viewfinder at centre) (3) Spot metering: Centre spot metering (approx. 2.7% viewfinder at centre) AF point-linked spot metering not provided (4) Centre weighted average metering		
<b>Metering Brightness Range</b>	EV -3 to 20 (at 23 °C, ISO 100, with evaluative metering)	<b>FLASH</b>	
<b>AE Lock</b>	Auto: AE lock takes effect when focus is achieved Manual: By AE lock button in P, Av, Fv, Tv and M modes	<b>Modes</b>	E-TTL II Auto Flash, Metered Manual
		<b>X-sync</b>	1/200sec
<b>Exposure Compensation</b>	+/-3 EV in 1/3 or 1/2 stop increments (can be combined with AEB)	<b>Flash Exposure Compensation</b>	+/- 3 EV in 1/3 increments with EX series Speedlite flashes
<b>AEB</b>	+/-3 EV in 1/3 or 1/2 stop increments	<b>Flash Exposure Bracketing</b>	Yes, with compatible External Flash
<b>Anti-flicker shooting</b>	Yes. Flicker detected at a frequency of 100 Hz or 120 Hz. Maximum continuous shooting speed may decrease	<b>Flash Exposure Lock</b>	Yes
		<b>Second Curtain Synchronisation</b>	Yes, via Speedlite
<b>ISO Sensitivity (8)</b>	Auto 100-40000 (in 1/3-stop or whole stop increments) ISO can be expanded to L:50, H1: 51200, H2: 102400	<b>Hot Shoe / PC terminal</b>	Yes / No
		<b>External Flash Compatibility</b>	E-TTL II with EX series Speedlite, wireless multi-flash support
<b>SHUTTER</b>		<b>External Flash Control</b>	Via camera menu screen
<b>Type</b>	Electronically controlled focal-plane shutter		
<b>Speed</b>	30-1/8000 sec (1/2 or 1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)		
<b>Shutter Release</b>	Soft touch electromagnetic release		

**Canon**

Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS R

# CAPTURE THE FUTURE

## SHOOTING

### Modes

Stills: Scene Intelligent Auto, Flexible priority AE, Program AE, Shutter priority AE, Aperture priority AE, Manual, Bulb and Custom (x3)  
Movie: Scene Intelligent Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Bulb and Custom (x3)

### Picture Styles

Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)

### Colour Space

sRGB and Adobe RGB

### Image Processing

Highlight Tone Priority  
Auto Lighting Optimizer (4 settings)  
Long exposure noise reduction  
High ISO speed noise reduction (4 settings) (still and video)  
Lens optical correction (3):  
- Peripheral illumination correction, Chromatic aberration correction Distortion correction (during/after still photo shooting, during video only)  
- Diffraction correction, Digital Lens Optimizer (during/after still photo shooting)  
Resize to M, S1, S2 (6)  
Cropping: JPEG images can be cropped (Aspect ratios 3:2, 4:3, 16:9, 1:1)  
- 45 cropping sizes selectable, from 11% to 95% (diagonal)  
- Switch between vertical and horizontal cropping orientation  
- Image straightening  
- Cropping frame can be moved using touch screen operation  
RAW image processing (7)  
Multiple exposure  
HDR

### Drive modes

Single, Continuous High, Continuous Low, Silent Single, Self timer (2s+remote, 10s+remote)

### Continuous Shooting

Max. Approx. 8fps. speed maintained for 100 JPEG or 47 RAW images (1) (2) (10)  
Max. 5fps with AF Tracking

### Interval timer

Not supported

## LIVE VIEW MODE

### Type

Electronic viewfinder with image sensor

### Coverage

Approx. 100% (horizontally and vertically)

### Frame Rate

59.97 fps (smooth) / 29.97 fps (power saving)

### Focusing

Manual Focus (Magnify the image 5x or 10x at any point on screen)  
Autofocus: Dual Pixel CMOS AF (Face Detection and Tracking AF, 1point AF, Expand AF Area Zone AF, and Touch shutter

### Metering

Real-time evaluative metering with image sensor (384-zone)  
Partial metering (approx. 6.1% of the centre of the screen)  
Spot metering (approx. 2.7% of the centre of the screen)  
Centre-weighted average metering  
Active metering timer can be changed

### Display Options

3 levels available Basic shooting information, Advanced shooting information and Advanced shooting information with Histogram

## FILE TYPE

### Still Image Type

JPEG: 2 compression options  
RAW: RAW, C-Raw and Dual Pixel RAW (14-bit, Canon original RAW 3rd edition)  
Complies with Exif 2.31 and Design rule for Camera File system 2.0  
Complies with Digital Print Order Format [DPOF] Version 1.1

### RAW+JPEG simultaneous recording

Yes, any combination of RAW + JPEG possible, including Dual Pixel RAW + JPEG

## Image Size

### JPEG:

3:2 ratio (L, RAW, C-Raw) 6720x4480, (M1) 4464x2976, (S1) 3360x2240, (S2) 1696x1280  
1.6x (crop) (L) 4176x2784, (S2) 2400x1600  
4:3 ratio (L) 5952x4480, (M1) 3968x2976, (S1) 2976x2240, (S2) 2112x1600  
16:9 ratio (L) 6720x3776, (M1) 4464x2512, (S1) 3360x1888, (S2) 2400x1344  
1:1 ratio (L) 4480x4480, (M1) 2976x2976, (S1) 2240x2240, (S2) 1600x1600

## EOS Movie

### Movie Type

MOV Video: 4K (16:9) 3840 x 2160, Full HD, HD  
MPEG4 AVC/H.264 variable (average) bit rate,  
Audio: Linear PCM

### Movie Size

4K (16:9) 3840 x 2160 (29.97, 25, 24, 23.98 fps) intra or inter frame (13)  
Full HD (16:9) 1920 x 1080 (59.94, 50, 29.97, 25, 23.98 fps) intra or inter frame (13)  
Full HD (16:9) 1920 x 1080 HDR (29.97, 25 fps) inter frame (13)  
Full HD (16:9) 1920 x 1080 (29.97, 25) light inter frame HD (16:9) 1280 x 720 (119.9, 100 fps) intra frame

### Colour Sampling (Internal recording)

4K - YCbCr4:2:2 (8-bit)

### Canon Log

Full HD/HD - YCbCr4:2:0 (8-bit)

### Movie Length

Yes, Log 1  
4K and Full HD - Max duration 29min 59sec. (excluding High Frame Rate movies). No 4GB file limit with exFAT CF card.

### High Frame Rate Movie

MOV Video: HD - 1280 x 720 at 100fps or 119.9fps  
Recorded as 1/4-speed slow motion movie  
Single scene maximum recording up to 7min 29sec.

### 4K Frame Grab

8.3-megapixel JPEG still image frame grab from 4K movie possible

### Bitrate/Mbps

MOV:  
4K (29.97p/25.00p/24.00p/23.98p): ALL-I Approx. 480 Mbps  
4K (29.97p/25.00p/24.00p/23.98p): IPB Approx. 120 Mbps  
Full HD (59.94p/50.00p)/ALL-I: Approx. 180 Mbps  
Full HD (59.94p/50.00p)/IPB Approx. 60 Mbps  
Full HD (29.97p/25.00p/24.00p/23.98p)/ALL-I: Approx. 90 Mbps  
Full HD (29.97p/25.00p/24.00p/23.98p)/IPB: Approx. 30 Mbps  
HD (119.9p/100.0p)/ALL-I: Approx. 160 Mbps  
MP4:  
Full HD (29.97p/25.00p)/IPB (Light): Approx. 12 Mbps  
Built-in stereo microphones (48 Khz, 16-bit x 2 channels)

### Microphone

External Monitor only, External Monitor only without information display or Simultaneous on camera and external monitor

### HDMI Display

External Monitor only, External Monitor only without information display or Simultaneous on camera and external monitor

### HDMI Output

4K (UHD) recording only, uncompressed YCbCr 4:2:2, 8-bit or 10-bit, sound output via HDMI is also possible

### Focusing

Dual Pixel CMOS AF with Face Detection and Tracking AF, Movie Servo AF  
Manual Focus

### ISO

4K - Auto: 100-12800, H: 25600, H1: 32000, H1: 51200, H2: 102400,  
Full HD/HD - Auto: 100-25600, H: 32000, H1: 51200, H2: 102400

## OTHER FEATURES

### Custom Functions

22 Custom Functions

### Metadata Tag

User copyright information (can be set in camera)  
Image rating (0-5 stars)  
IPTC data (registered with EOS Utility)  
Image transfer with caption (Caption registered with EOS Utility)

### LCD Panel / Illumination

Yes / Yes



Live for the story\_

# TECHNICAL SPECIFICATIONS

# EOS R

# CAPTURE THE FUTURE

<b>Water/Dust resistance</b>	Yes	<b>SOFTWARE</b>	
<b>Voice Memo</b>	No	<b>Image Processing</b>	Digital Photo Professional 4.9 or later (RAW Image Processing)
<b>Intelligent Orientation Sensor</b>	Yes	<b>Other</b>	EOS Utility 3.9 or later (incl. Remote Capture), Picture Style Editor, Map Utility, EOS Lens Registration Tool, EOS Web Service Registration Tool, Canon Camera connect app (iOS/Android)
<b>Playback zoom</b>	1.5x - 10x in 15 steps		
<b>Display Formats</b>	(1) Single image (2) Single image with information (2 levels) Basic - Shooting information (shutter speed, aperture, ISO and Image quality) Detailed - Shooting information (shutter speed, aperture, ISO, metering Image, quality and file size), Lens information, Brightness and RGB histogram, White balance, Picture Style, Color space and noise reduction, Lens optical correction, GPS information, IPTC information (3) 4 image index (4) 9 image index (5) 36 image index (6) 100 image index (7) Jump Display (1, 10 or 100 images, Date, Folder, Movies, Stills, Protected images, Rating) (8) Movie edit (9) RAW processing (10) Rating	<b>POWER SOURCE</b>	
<b>Slide Show</b>	Image selection: All images, by Date, by Folder, Movies, Stills, Protected images or Rating Playback time: 1/2/3/5/10 or 20 seconds Repeat: On/Off	<b>Batteries</b>	Rechargeable Li-ion Battery LP-E6N (supplied)/LP-E6
<b>Histogram</b>	Brightness: Yes RGB: Yes	<b>Battery life</b>	Approx. 370 shots (at 23°C) (5) Approx. 350 (at 0°C)
<b>Highlight Alert</b>	Yes	<b>Battery Indicator</b>	6 levels + percentage
<b>Image Erase</b>	Single image, select range, Selected images, Folder, Card	<b>Power saving</b>	Power turns off after 30 seconds, 1, 3, 5, 10 or 30 mins
<b>Image Erase Protection</b>	Erase protection of Single image, Folder or Card all found images (only during image search)	<b>Power Supply &amp; Battery Chargers</b>	Battery charger LC-E6E (supplied), AC Adapter AC-E6N and DC Coupler DR-E6, AC Adapter Kit ACK-E6N/ACK-E6, Car Battery Charger CBC-E6, USB power adapter PD-E1
<b>Self Timer</b>	2 or 10 sec.		
<b>Menu Categories</b>	(1) Shooting menu (2) AF Menu (3) Playback menu (4) Setup menu (5) Custom Functions menu (6) My Menu	<b>PHYSICAL SPECIFICATIONS</b>	
<b>Menu Languages</b>	29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Vietnamese, Hindi, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Indonesia and Japanese	<b>Body Materials</b>	Magnesium Alloy body and polycarbonate with glass fibre parts
<b>Firmware Update</b>	Update possible by the user (Camera, Lens, WFT, External Speedlite, BLE remote control, Lens adapter)	<b>Operating Environment</b>	0 - 40 °C, 85% or less humidity
<b>INTERFACE</b>		<b>Dimensions (WxHxD)</b>	135.8 x 98.3 x 84.4mm
<b>Computer</b>	SuperSpeed USB 3.1 USB C connector	<b>Weight (body only)</b>	Approx. 580 g (660 g with card and battery)
<b>Wi-Fi</b>	Wireless LAN (IEEE802.11b/g/n) (2.4 GHz only), with Bluetooth support [12] Features supported - EOS Utility, Smartphone, Upload to Web, Wireless printing	<b>ACCESSORIES</b>	
<b>Other</b>	HDMI mini out (Type C, HDMI-CEC compatible), External Microphone In/Line In (Stereo mini jack), Headphone socket (Stereo mini jack), E3-type terminal (remote control terminal)	<b>Wireless File Transmitter</b>	Wireless File Transmitter WFT-E7B
<b>DIRECT PRINT</b>		<b>Lenses</b>	All RF lenses (EF & EF-S via Lens adapters)
<b>PictBridge</b>	Yes (via wireless LAN only)	<b>Lens adapters</b>	Mount Adapter EF-EOS R, Control Ring Mount Adapter EF-EOS R, Drop-In Filter Mount Adapter EF-EOS R
<b>STORAGE</b>		<b>Flashes</b>	Canon Speedlite (EL-100, 90EX, 220EX, 270EX, 270EX II, 320EX, 380EX, 420EX, 430EX, 430EX II, 430EX III 470EX-AI, 550EX, 580EX, 580EX II, 600EX, 600EX-RT, 600EX-II-RT, Macro-Ring-Lite MR-14EX, Macro Ring Lite MR-14EX II, Macro Twin Lite MT-24EX, Macro Twin Lite MT-26EX Speedlite Transmitter ST-E2, Speedlite Transmitter ST-E3-RT)
<b>Type</b>	1x SD/SDHC/SDXC and UHS-II	<b>Remote Controller/Switch</b>	Remote control with E3 type socket and Speedlite 600EX-II-RT, Wireless Remote Control BR-E1
<b>SUPPORTED OPERATING SYSTEMS</b>		<b>Other</b>	Battery grip BG-E22, GP-E2 GPS receiver
<b>PC &amp; Macintosh</b>	Windows 7 (excl. Starter Edition) Windows 8.1 and Windows 10 (tablet mode not supported) OS X v10.11, 10.12, 10.13 and 10.14		

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

1 Large/Fine resolution

2 Based on Canon's testing conditions, JPEG, ISO 100, Standard Picture Style.

Maximum fps and buffer capacity may be reduced depending on the cameras settings, light level, subject, memory card brand and capacity, image recording quality, ISO speed, drive mode, Picture Style, Custom functions etc.

4 with 50mm lens at infinity, -1m-1 dpt

5 Based on the CIPA Standard and using the battery supplied with the camera, except where indicated

6 Frame grab images from 4K movies and images shot in S2 quality cannot be resized

7 RAW image processing during image Playback only with RAW and Dual Pixel RAW only

8 Recommended Exposure Index

10 Figures quoted are when used with USH-II SD memory card

11 The AF area available vary depending on the lens used

12 Wi-Fi use may be restricted in certain countries or regions

Live for the story\_

# EOS R

CAPTURE THE  
FUTURE

Sales Start Date: Early October 2018



## PRODUCT DETAILS:

Product Name	Mercury Code	GTIN Code	Recommended Retail Price
EOS R BODY + Mount Adapter EF-EOS R	3075C061AA	8714574659978	£2349.99 / €2729.99
EOS R RF24-105mm f/4 L IS USM + Mount Adapter EF-EOS R	3075C059AA	8714574659640	£3269.99 / €3819.99

## OPTIONAL ACCESSORIES:

Product Name	Mercury Code	GTIN Code
Lens RF50mm f/1.2 L USM	2959C005AA	4549292115581
Lens RF24-105mm f/4 L IS USM	2963C005AA	4549292115611
Lens RF28-70mm f/2 L USM	2965C005AA	4549292115642
Lens RF35mm f/1.8 Macro IS STM	2973C005AA	4549292115727
Mount Adapter EF-EOS R	2971C005AA	4549292115703
Control Ring Mount Adapter EF-EOS R	2972C005AA	4549292115710
Drop-In Filter Mount Adapter EF-EOS R with Drop-In Circular Polarizing Filter A	3442C005AA	4549292141603
Drop-In Filter Mount Adapter EF-EOS R with Drop-In Variable ND Filter A	3443C005AA	4549292141610
Drop-In Clear Filter A	3444C001AA	4549292141627
Drop-In Circular Polarizing Filter A	3445C001AA	4549292141634
Drop-In Variable ND Filter A	3446C001AA	4549292141641
Battery Grip BG-E22	3086C003AA	4549292119930
Neck Strap ER-100B	3222C001AA	4549292124187
USB Power Adapter PD-E1	3250C003AA	4549292125412
Flash Speedlite EL-100	3249C003AA	4549292125450
Interface Cable IFC-100U	3224C001AA	4549292124200
Interface Cable IFC-400U	3225C001AA	4549292124224
Interface Cable IFC-40AB III	3226C001AA	4549292124248
Interface Cable IFC-150AB III	3227C001AA	4549292124262
Wireless Remote Control BR-E1	2140C001AA	4549292087864

**Canon**

Live for the story\_

# EOS R

# CAPTURE THE FUTURE

## MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Gross Weight (kg)
EOS R BODY + Mount Adapter EF-EOS R	EA	Each	1	28	22.3	14.7	1.629
	CT	Carton	6	47.7	47.1	31.4	11.10
	EP	Euro Pallet	36	120	80	109.2	76.6
		Layers per Pallet	3				
		Cartons per Layer	2				
		Products per layer	12				
EOS R RF24-105mm f/4 L IS USM + Mount Adapter EF-EOS R	EA	Each	1	36.5	22.6	18.7	2.648
	CT	Carton	2	60	40	40	6.45
	EP	Euro Pallet	16	120	80	95	61.6
		Layers per Pallet	2				
		Cartons per Layer	4				
		Products per layer	8				

## What's in the box?

### EOS R BODY + Mount Adapter EF-EOS R

- EOS R Body
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- AC Cable
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- Mount Adapter EF-EOS R
- Lens Dust Cap RF
- Camera Cover R-F-3
- User Manual Kit

### EOS R + RF24-105mm f/4 L IS USM + Mount Adapter EF-EOS R

- EOS R Body
- Camera Cover R-F-5
- Strap ER-EOSR
- Battery Charger LC-E6E
- Battery Pack LP-E6N
- AC Cable
- Interface Cable IFC-100U (No core)
- Interface Cable IFC-100U protector
- RF24-105mm f/4 L IS USM
- Lens Cap E-77 II
- Lens Dust Cap RF
- Lens Hood EW-83N
- Lens Case LP1319
- Mount Adapter EF-EOS R
- Lens Dust Cap RF
- Camera Cover R-F-3
- User Manual Kit

Live for the story\_